



INTRODUCING OUR NEW  
**INVERTER RANGE**  
12 000 / 18 000 / 24 000 BTU



- Dual Cool Inverter
- Sleep Mode
- 40% Faster Cooling
- Safety Design
- 5 Year Compressor Warranty
- 60% Energy Saving



allairaircon.co.za  
012 644 1525



Nominal Capacity		12K	18K	24K
Model		UNI-RAC12I	UNI-RAC18I	UNI-RAC24I
Power Supply		Ph-V-Hz	1Ph / 220-240V/50Hz	1Ph / 220-240V/50Hz
Capacity		BTU/H	12000 (2700-13000)	18000 (2700-19000)
Cooling	Capacity	W	3500 (880-3810)	5250 (1320-5570)
	Working Voltage	V	150-260	150-260
	Rated Current	A	5.0 (0.9-7.8)	7.5 (1.4-11.6)
	EER	W/W	3,38	3,28
	Input	W	1050 (200-1690)	1600 (300-2500)
	Max Current	A	7.90	12.40
Heating	Capacity	BTU/H	12000 (2700-13000)	18000 (2700-19000)
	Capacity	W	3550 (880-3810)	5275 (1320-5570)
	Working Voltage	V	150-260	150-260
	Input	W	1200 (200-1690)	1600 (300-2500)
	Rated Current	A	5.0 (0.9-7.8)	7.5 (1.4-11.6)
	COP		3,27	3,30
Max. Input Consumption		W	1650	2500
Max. Current		A	8,5	11,6
Compressor	Type		Rotary	Rotary
	Model		KSKI03D26UEZD3	C-6RZ132H3BAF
	Brand		GMCC	SANYO (CRSS)
Indoor Unit	Indoor Coil	Fin Material	Hydrophilic	Hydrophilic
		Tube Outside Dia. & Material	φ7mm, Inner Grooved	φ7mm, Inner Grooved
	Indoor Air Flow (Hi/Mi/Lo)	M3/H	650/550/480	800/600/550
	Rated Input Power (Cooling/Heating)	W	35	50
	Rated Current (Cooling/Heating)	A	0,2	0,25
	Moisture Removal	(KG/H)	1,1	2
	Noise Level (Hi/Mi/Lo)	dB	39/37/34	45/42/39
	Unit Dimension (W*H*D)	mm	800x292x190	850x292x190
	Packing (W*H*D)	mm	865x335x240	915x335x240
	Net Weight	KGS	8,5	9
Gross Weight	KGS	10	11	
Outdoor Unit	Outdoor Coil	Fin Material	Hydrophilic	Hydrophilic
		Tube Outside Dia. & Material	φ7mm, Inner Grooved	φ9.52mm, Inner Grooved
	Noise Level (Hi/Mi/Lo)	dB	47	53
	Unit Dimension (W*H*D)	mm	740x256x551	800x551x256
	Packing (W*H*D)	mm	810x355x595	870x355x595
	Net Weight	KGS	32	37,5
	Gross Weight	KGS	33	40,5
Refrigerant Type		R410A	R410A	
Refrigerant Pipe	Liquid Side	mm	φ6.35	φ6.35
	Gas Side	mm	φ9.52	φ12.7
	Max. Refrigerant Pipe Length	m	10	10
	Max. Difference In Level	m	5	5
Operation Temperature Range			-8°C-38°C	-8°C-40°C
Ambient Temperature Range			-8°C-42°C	-8°C-42°C
Application Area (mm <sup>2</sup> )			14~21	20~40
Sets Per 40ft HQ			305	280



**HOT. COLD. SORTED.**